



## Release Notes

Version	Date	Illustrated articles
<a href="#">11.1.11404</a>	March 23 <sup>th</sup> 2026	
<a href="#">11.1.11355</a>	February 2 <sup>nd</sup> 2026	
<a href="#">11.1.11278</a>	November	<a href="#">What's new in 11.1</a>
<a href="#">11.0.11215</a>	September 15 <sup>th</sup> 2025	
<a href="#">11.0.11155</a>	July 17 <sup>th</sup> 2025	
<a href="#">11.0.11118</a>	June 10 <sup>th</sup> 2025	<a href="#">What's new in 11.0</a>

Digital Surf Software Updates  
[www.digitalsurf.com/support/software-updates](http://www.digitalsurf.com/support/software-updates)

Digital Surf Support solutions  
[www.digitalsurf.com/support/support-solutions](http://www.digitalsurf.com/support/support-solutions)

Digital Surf FAQ  
[www.digitalsurf.com/support/faq](http://www.digitalsurf.com/support/faq)

Support Center  
[support.digitalsurf.com](http://support.digitalsurf.com)

## Bug corrections (A and B type)

	Type	Bug Description
MNT-12896	A	The residue is not displayed and the RON parameters of the ISO 12181 standard are not calculated in the "Advanced contour analysis study" on Contour profile studiabes when saving and then reloading the document.
MNT-12911	A	The software may crash when deleting a "CAD compare" study on Shell studiabes if the study has been duplicated.
MNT-12915	A	The 3D views do not display and the software may crash if the path to the Mountains® document contains Asiatic characters.
MNT-12962	A	The software may crash when hovering the mouse over a Python addon (study or operator) or when recalling a Python addon operator if the Python version used is 1.13.
MNT-12975	A	Mountains cannot read a license validity if the SMP (Software Maintenance Plan) date is beyond January 19, 2038.
MNT-13054	A	Validating the "Level" operator dialog box on Profile studiabes using the "Total least squares (TLSLI)" method and disabling the "Set the origin of the Z-axis as the mean of the included zones" option does not produce the same results as applying these same parameters on the Profile studiabes after saving them. The results are also not identical when reopening the document.
MNT-13173	A	The axis of rotation of the cylinder in the preview results "Mesh + deviations" in the dialog box of the operator "Fit a geometric form" on Shell studiabes is incorrect if the "Least squares cylinder" option is selected.
MNT-13229	A	STL files are always loaded as Shell studiabes, irrespective of whether or not that is the correct data type or if the product can handle that type of studiabile.
MNT-12155	B	The X, Y and W-planes can no longer be moved using the arrow keys in 3D view studies on Hyperspectral image studiabes.
MNT-12834	B	The tolerances on deviation shown for the drawing of circles when using a "Circle (from closed profiles)" element in the "Advanced contour analysis" study on Contour profile studiabes are erroneous.
MNT-12869	B	A band observed when the "Apply in real time" option is checked in the "Canny Detection" dialog box of the [Canny Edge Detection] button in the "Line Edge Roughness Analysis" study on Image studiabes is no longer detected when validating the dialog box.
MNT-12882	B	The contour drawing is incorrect in the "Extract local contour" operator on Surface studiabes when using the "Outlier cleaning" option on the "Parallel contour profiles" extraction shape.
MNT-12886	B	TIFF files can be loaded as Surface studiabes instead of image studiabes if there is Z axis information in the file, whether or not the Z axis is in a length unit.
MNT-12895	B	It is possible to create a "Force curve analysis" study by selecting two force volume studiabes (instead of creating two "Force curve analysis" studies, one for each selected studiabile).
MNT-12897	B	The icons of the Selection and Dimensional tools in the "Advanced contour analysis" study are incorrectly redisplayed when changing the Unit system between Metric units and Imperial units in the Global preferences of the software.
MNT-12901	B	The names of the elements in the Series for force curves or Force volume studiabes are not saved in the documents if they have been modified in the "Rename the elements of the studiabile" dialog box of the studiabile from the workflow.
MNT-12903	B	The lowest point does not appear in the extracted surface studiabile generated by the "Extract projected surface" operator on Point cloud studiabes.
MNT-12904	B	A retract point of the previous segment is assigned to an empty segment in the "Force curve analysis" study on Force curve-type studiabes when copying the "With corrected segments" studiabile (or when opening a document containing a studiabile of this type).

MNT-12906	B	The "Cantilever spring constant" on Force curve, Series of force curves and Force volume studiabes is lost on .BCRF format files.
MNT-12916	B	The 3D view study on Surface, Image, Surface + image, Series of surface, Multi-channel image, Shell, Hyper spectral image and IV spectroscopy image studiabes may be incorrectly reconstructed in the "Remove form" operator after a change in the workflow.
MNT-12918	B	The "Summary of the current operator" study can show partial results of a different zone if the "Extract areas" operator is called twice.
MNT-12940	B	It is not possible to enter values in the combo-box of the option "Use Z axis origin as the reference height" of the "Step width section in the "Settings" dialog box of the "Step height" study in Profile studiabes.
MNT-12951	B	The Undo/Redo function does not work when defining a tolerance limit from the 'Tolerance limits' manager dialog box in the Result Manager contextual menu.
MNT-12951	B	The Undo/Redo function does not work when defining a tolerance limit from the 'Tolerance limits' manager dialog box in the Result Manager contextual menu.
MNT-12956	B	A crash may occur when loading a document containing add-ons if the document was created in a later version of Mountains and is loaded in a previous released version.
MNT-13000	B	The bottom vertical cursor of the mask preview's vertical palette is difficult to select in the "Apply mask of non-measured points" operator dialog box on Surface, Surface + image and Multi-channel image studies if it overlaps with the top cursor.
MNT-13002	B	The settings dialog box of the "Lead twist" analysis study does not open anymore when launching the Smartflow by a command file.
MNT-13022	B	It is not possible to load an RGB image containing more than 715 million pixels.
MNT-13123	B	The "Convert W-axis" operator on Spectrum curve and Hyperspectral image studiabes does not function if the units of the Z-axis are in "count/pm" (metric units).
MNT-13185	B	The display of results in the "Hyperspectral image view" study on Hyperspectral image studiabes is incorrect after insertion of the "Normalize spectrum curves" operator from the workflow with the choice of the SNV (Standard Normal Variate) normalization method.
MNT-13055	B	Copying a 3D view study and pasting it into a new illustration as a bitmap image displays multiple, overlapped copies of the 3D view study.

## What's new

	<a href="#">Ergonomics and automatic updates in the "Stitch" operator</a>
Ergonomics in the "Stitch" operator	The user interface for the selection modes in the "Stitch" operator has been standardized. A distinction was introduced between manual selection and automatic selection in order to facilitate understanding of the selection and filtering of the studiables.
Automatic updates to the previous studiables in the "Stitch" operator	The list of previous studiables of the selected studiables (root or leaf, meeting the criteria for potential filtering) in the "Stitch" operator present in a document is now automatically updated (during application in SmartFlow/Analysis examples, loading of studiable, insertion of an operator, renaming of studiables...)
	<a href="#">Other general features</a>
Changing studies names	It is now possible to define a new name for studies, just as it is for studiables. This new custom name will be retained when using automation features (analysis examples, SmartFlows, substitution). The modified names are also displayed in the Result Manager, the "History of current studiable" study, in statistical studies and statistical documents. The name obtained via the COM interface IXOperatorNode::get_Name is also affected.
Partially transparent Addons	It is now possible in Addons studies to define the areas (rectangles) within which the study is drawn. This allows users, for example, to create Addons studies that automatically draw based on page changes (useful for large tables that don't fit on one page).
Loading profilometry data as Surface + image or multiple studiable	Where appropriate, profilometry data (notably DATx files from Zygo instruments) is now loaded either as a Surface+image studiable or as multiple root studiables.

## Bug corrections (A and B type)

	Type	Bug Description
MNT-12677	A	The software may crash when loading a Spectrum curve studiable with coordinates (W, Z) from a text file if the Z axis information is in the 5th column.
MNT-12760	A	The software may crash when applying the "Mesh the point cloud" operator on a Point cloud studiable containing few points.
MNT-12317	B	The "Spherical caps" feature does not detect the lower caps of the spheres in the "Particle analysis" study on Surface, Image, and Multichannel image studiables when the "Threshold Detection" method is selected.
MNT-12639	B	The management of non-measured points is incorrect when applying the "Detect structure" operator on studiables containing a large number of non-measured points. It applies to Image, Surface and Multi-channel image studiables.
MNT-	B	It is impossible to load studiables in FITS file format if the file size exceeds 5 GB.

12692		
MNT-12722	B	The "Generate whole content" button in the "Colocalization" study on Image studiables does not work in the MountainsSEM® Color product.
MNT-12732	B	Loading a studiable in ASCII format does not work correctly if the date of the file is January 1, 1970.
MNT-12735	B	The topography channel is not read in .NHF files.
MNT-12737	B	Applying the "Correct the shell" operator on Shell studiables does not correct duplicate vertices.
MNT-12764	B	It is not possible to save a document containing a Profile studiable in PDF format if the "Imposed range" option is selected for the vertical axis (Z) of the profile in the "Axis settings" dialog box.
MNT-12771	B	The width of the Custom bands in the "Level line by line" operator on Surface and Multi-channel image studiables changes with orientation, and cannot be modified if the band is positioned horizontally or vertically.
MNT-12773	B	The W-axis is exported in mm (instead of nm) when the "Export curve" button is pressed or the "Fill/Save the spectrum curve" menu option is used on a Spectrum curve studiable.
MNT-12774	B	The text content pasted into the clipboard of the "Parameters Table" study on "Profile" studiables is not up to date when the studiable used for calculations is displayed in the study.
MNT-12815	B	The "Studies" and "Operators" menu tabs do not appear when using the command "LOAD_STUDIABLE" in a command file.
MNT-12857	B	The copied current workflow selection is not retained when switching from one open document to another.
MNT-12674	B	The center of rotation of the "3D view of the multi-channel image" study is not correctly centered in the "IV Spectroscopy Analysis" document accessible via the "Analysis Examples" menu in the "Help" tab.

## What's new

	<b>Multi-technology features</b>
	<b>Enhanced positions in 3D studies</b>
'Free rotation' mode in 3D views	In studies showing 3D views, it is now possible to rotate 3D views at any orientation, even on the side. The constrained mode keeping the camera upright, is still available for surfaces, and has been added on Shells and Point clouds
'Orthographic' projection mode in 3D views	In studies showing 3D views, perspective can now be removed to obtain an orthographic projection.
Circle 2 Flight path for animation in 3D views	In studies showing 3D views, a "Circle 2" (less inclined) Flight path animation is now available.
Dimension block in color in 3D views	In studies showing 3D views, it is now possible to choose the font color of the Dimension block.
	<b>AI segmentation and improved navigation in the "Particle analysis" study</b>
AI segmentation in the "Particle analysis" study	A new segmentation method using neural networks has been added to the "Particle analysis" study. The method is applicable to round and compact particles, but also to particles of various shapes. It is very effective for contiguous particles. The AI segmentation method dialog allows the user to: Pre-process the image using a smoothing filter, Guide the algorithm to an order of magnitude of the particles size (in case of limitations of the completely automatic method), and Fine tune the quantity of points to be included into the particles. This applies to Surface, Surface + image, Image and Multi-channel image studiables.
Visualization of small particles in "Particle analysis" study	The particle label is now displayed on the "Particle analysis" study image when selecting a row in the study's results table. Clicking on the label in the image displays the zoomed particle and, temporarily, the inspection box. This makes it easier to navigate and zoom in on small particles.
	<b>Modernized Load and Save dialogs</b>
Document and studiable visualizations in load and save dialogs	The dialogs for opening documents, loading studiables, and exporting images now enables the user to preview the document or studiable in bigger size.
Windows explorer Quick access and theme in Open and Save dialogs	The Open and Save dialogs have been updated to the latest Windows style, allowing the user's Windows explorer Quick access, and following the Windows theme. To maintain all functionalities, text, options, sub-menus and checkboxes have been added to the open and save dialogs. This applies to the following dialogs: Load/Save a studiable, Open/Save a document, Export results, Apply a template, Substitute the current document, Open/Save Background page, Export the document as one image per page, Export frame as image, Select a folder for the Smartflow manager, Statistical population, Select dynamic statistical population, Import/Export of statistical definition text files (STS), Select a folder for profilometers, Select a folder for settings, Select a folder for the particle classification manager, Import/Export DXFs into the "Advanced contour analysis" study, Export contour deviations.
Shortcuts to Example studiables, templates and tutorials in the opening dialogs	The Load a studiable dialog now contains shortcuts to Example studiables folder. The Open a document dialog now contains shortcuts to the example documents and tutorials folders.
Exported image resolution preview	By changing the resolution in the image export dialog, the user can preview the result in real time in the preview.

	<b>Automatic color in frames</b>
Automatic color in frames	In frames (studies or illustrations), some color settings can use an Automatic color setting, to avoid having to change several settings when changing the background color of the frame. The Automatic color is set by default. See details below.
Automatic colors for text and lines	In studies, text and axis lines can now take an automatic contrasting color to that of the background. This applies to: The text and numbers of: Title, Graduations, Color scale, Dimension block in 3D, Tolerance limits text, Buttons, Date and Page number illustrations, Warning texts, Frame number. The lines of: Axis, Grid, Color scale outline, Box plots outline, Fractal regression line, Abbott curve and Histogram bars and outlines, Point cloud points This does not apply to the "Advanced contour analysis" study.
Automatic color for fill-in	In studies, some color settings used to fill-in portions of the frame can now use an automatic color: In 3D view, the automatic axis plane color (scale markers) is a color gradient of the Frame fill color. For graph visualization (Profile, Series of profiles, Spectrum, etc.), the automatic Graph fill color is the Frame fill color. The automatic Legend color is the Frame fill color. For image visualization (surface, image, force-Volume, etc.), the automatic Image fill color is either black or white depending on the Frame fill color.
	<b>Other</b>
Priority position of frames	The Priority position frame property places the frames having this property in front of the frames without this property. The Priority position property is enabled by default for all Illustrations except the Color background Illustration.
Default selection mode after creating a new shape in operators	In the "Extract areas" operator dialog, at the end of creating a new area to extract, selection mode is automatically restored, to prevent the inadvertent creation of new elements. This applies to Surface, Surface + image, Series of surfaces, Multi-channel image, Force volume, Hyperspectral image and IV spectroscopy image studiables. The same behavior applies to the "Extract profiles" and "Extract series of profiles" operators. This applies to Image, Surface, Surface + image, Series of surfaces and Multi-channel image studiables.
Transparent text box	It is now possible to directly insert a transparent text box without outline
Visibility of Blocks and planes panel in the 3D view on Multi-channel cubes	The Blocks and planes panel is now displayed by default in the "3D view of the cube" study on Multi-channel cube studiables.
Frame number in multi-selection	The frame number is now displayed when selecting several frames.
Enrichment of Help/Support package	The Support package has been enriched with information about installation and license. A dialog has been added, to possibly add dumps files (to fix software crashes), and unsaved Mountains documents.
	<b>Profilometry features</b>
	<b>AI segmentation in the "Particle analysis" study</b>
AI segmentation in the "Particle analysis" study on topography	The AI segmentation method (described above in the "Multi-technology" section), can be applied to topography surfaces. Compared to other methods, it is particularly useful for agglomerated particles on a visible background.
	<b>"Extract local contour" operator improvements</b>
Better automation in the "Extract local contour" operator	In the Derivative detection method in the "Extract local contour" operator, the user can now choose to define the threshold of the derivative with an absolute value of local slope rather than a percentage. This is useful for automation.
Exclusion of outliers in the "Extract local contour" operator	In the Derivative detection method in the "Extract local contour" operator, an Outlier cleaning slider allows the user to discard a certain percentage of contour points whose slope is below the mean slope of all contour points. This applies to Surface, Image and Surface + image studiables
Circular residue by subtraction in the "Remove form" operator on Profiles	In the "Remove form" operator on Profile studiables, for circular form, the user can now choose to calculate the residue by subtraction perpendicular to the Z axis (without unrolling the profile). This allows the initial length of the profile to be preserved.
Dilation of Non-measured points in the "Remove outliers" operator	In the "Remove outliers" operator, the user can now choose whether or not to delete points by dilating all original non-measured points of the source studiable.
S-filter information in the "Parameters table" study	Information has been added next to the S-filter checkbox in the dialog of the "Parameter table" study to explain the function according to the context.

	<h2>Shell and Point clouds</h2>
Improved optimization in the "Remesh the shell" operator on Shells	The Optimize function of the "Remesh the shell" operator on Shells has been improved. (The optimization reduces the number of triangles in flat areas while preserving the details where there are local curvature changes).
Better alignment in the "3D Stitch" operator	The pre-alignment on the "Stitch together in 3D space" operator on Point clouds or Surfaces is now faster and more precise.
Ergonomics in the "Remesh the shell" operator on Shells	The interface of the "Remesh the shell" operator dialog on Shell studiables has been simplified. The Reduce and increase settings have been merged in a Resample setting. The Optimize settings uses a slider rather than a drop-down menu.
Homogenization of operators on Shells	The dialogs of some operators on Shells now better follow dialog interface rules. For example, settings that affect the preview but not the generated studiables are placed in a preview button above the preview.
	<h2>SEM features</h2>
AI segmentation in the "Particle analysis" study on SEM images	The AI segmentation method (described above in the "Multi-technology" section), can be applied to SEM images. This AI segmentation method overcomes the limitations of classical Threshold or Watershed detection (ie challenging contrast, or particle overlap).
SEM-BSE dialog in "Particle analysis" study	The SEM-BSE segmentation dialog in the "Particle analysis" study on image (or image channel of MCI) has been homogenized with Multi-channel cubes.
	<h2>Spectroscopy features</h2>
XY cursor in the "Grid view" study on Multi-channel images	A common cross-hair XY cursor for all channels is available in the "Grid view" study on Multi-channel image studiables. The cursor can be positioned at an XY position and synchronized with those of other studies.
Quality factor parameter in the "Peak fitting" study on spectrum	The Quality factor parameter can now be calculated in the "Peak Fitting" study on Spectrum curves and Hyperspectral images. The Quality factor parameter is useful in the field of nanoIR to analyze resonance. ( $Q = f/\Delta f$ , where $f$ is the frequency at resonance (peak position) and $\Delta f$ is its bandwidth (FWHM)).
SHO model in the "Peak fitting" study on spectrum	The SHO modeling function can now be used to fit curve in the "Peak fitting" study on Spectrum curves and Hyperspectral images. The SHO (Simple harmonic oscillator) function is useful in the field of nanoIR to analyze resonance.
AI segmentation in the "Particle analysis" study on spectral maps	The AI segmentation method (described above in the "Multi-technology" section), can be applied to spectral maps.
	<h2>Licenses</h2>
Interface of the License information dialogue	The License information dialog has been modernized for better understanding. Additional information is now visible: Current version of Mountains, and (if connected to Internet) the Highest eligible version.
Question in Contact dialog	The Contact dialog available from the License information dialog has been modernized and now allows you to ask a question.
Online SMP renewal	The Software Maintenance Plan renewal dialog now contains a link to purchase the renewal on our online webstore.
Question in SMP renewal	The Contact dialog available from the Software Maintenance Plan renewal dialog has been modernized and now allows you to ask a question.
	<h2>Updates and translations for Interface &amp; Reference Guide</h2>
User interface	New texts related to new features have been added to the user interface (in English). They have been translated into the following languages: French, German, Italian, Spanish, Japanese, Chinese, Polish, Korean, Brazilian Portuguese. Note: A complete retranslation into Japanese is in progress. This means that the style and vocabulary might not be homogeneous for the moment.
Reference Guide	The Reference Guide has been updated with the descriptions of most new main features and improvements (in English). It has been translated into French and German. The Japanese translation will follow in a Service Pack. Note: A complete retranslation into Japanese is in progress. This means that the style and vocabulary might not be homogeneous for the moment (between Interface and Reference Guide, and inside the Reference Guide itself).

# Bug corrections (A and B type)

	Type	Bug Description
MNT-12132	A	The software may crash when opening the "Calibrate constants" operator dialog box on a Force volume studiable that does not contain a distance signal.
MNT-12196	A	A crash may occur when recalling the Extract profiles operator from the Summary of the current operator study if the operator dialog contains more than one profile and one of the extractions is deleted.
MNT-12252	A	The cursor on the W-axis in the "Peak fitting" study on Spectrum curve and Hyperspectral image studiabes does not follow the movement of the curve and axes.
MNT-12261	A	The result of the Detect structures operator using a reference structure may have incorrect axis sizes if the spacing of the points in the reference structure and the full source studiable is different. Affects Surface and Image studiabes.
MNT-12272	A	The results calculated in the "Parameters table" study on Series of profiles or Series of surfaces studiabes can be wrongly adapted to the length unit if choosing the Gaussian option for the 'S-filter ( $\lambda$ s)' in the operator dialog box.
MNT-12298	A	The calculation of the bandpass filtering on Surface studiabes is incorrect when applying the "Metrological filter" operator.
MNT-12355	A	The software may crash when applying the "Fill in holes" operator on Shell studiabes if substituting the studiable in a particular case.
MNT-12357	A	The software may crash when applying the "Fill in holes" operator as a Quick pre-processing operator on Shell studiabes.
MNT-12408	A	The software may crash when renaming a class in the Classification dialog box of the "Particle analysis" study on Surface, Surface + image, Image and Multi-channel image studiabes if the same name is assigned to two classes.
MNT-12420	A	The color of the pixels is incorrect in the "Image colorization" study on greyscale Image studiabes.
MNT-12555	A	The software may crash when loading a document containing the "Correct the shell" operator on Shell studiabes in a particular case.
MNT-12560	A	The original normals of the shells are not kept in the "Fill in Holes" operator on Shell studiabes.
MNT-3548	B	The size of the points comprising a Point Cloud studiable is too small to be easily seen when printing.
MNT-11348	B	The size of the extraction box in the "Extract area" operator on Point cloud studiabes cannot return to a manipulable size when one of the faces of the extraction box is modified.
MNT-11436	B	The [Enhancement] and [Studiable color] buttons are grayed out in the ribbon of the "Wear or deposit analysis" and "Thickness analysis" studies (2D and 3D views) on Surface studiabes. The [Show color scale for Z axis] (Palette group) button is grayed out in the "Thickness analysis" study (3D view) on Surface studiabes.
MNT-11442	B	The pre-defined 3D display of views on Surface studiabes does not display correctly when reloading a document.
MNT-11483	B	The position of the image-graph separation line in the "View of the hyperspectral image" and "Summary of the current operator" studies on Hyperspectral image studiabes is not preserved during a copy/paste operation.
MNT-11654	B	The "Automatic full screen" mode in the "CAD compare study" on Shell studiabes does not always work correctly.
MNT-11662	B	The definition for the Maximum caliber parameter in the "Particle Analysis" study in the Reference Guide is incorrect and corresponds to the Maximum Feret diameter instead.
MNT-11764	B	It is no longer possible to modify a custom path shape during its construction when applying the "Extract profiles" or "Extract areas" operators on Surface, Image, Surface +image, Multi-channel image, Hyperspectral image and IV spectroscopy image studiabes.
MNT-11774	B	The color of a shell studiable in 3MF format is not respected when loading into the software.
MNT-11841	B	The Use studiable properties option is available when it shouldn't be in the Grid wizard section of the "Stitch" operator dialog box on Surface, Image, Surface + image and Multi-channel image studiabes.

MNT-11853	B	The Extraction shape cannot be correctly manipulated in the "Extract projected surface" operator on Shell studiabes.
MNT-11942	B	The software is slow when a lot of addon parameters are displayed in "Parameters table" studies.
MNT-11993	B	The roughness profile is identical to the waviness and the source profiles (rather than being flat) if the cut-off is set to zero in the S-filter ( $\lambda_s$ ) section of the Select parameters dialog box of the "Parameters table" study on Profile studiabes.
MNT-12015	B	The transparency of the "3D view of the Surface + image" study uses the grayscale palette in the Color menu rather than the default palette on Surface + image studiabes.
MNT-12119	B	The "Incompatible document" band is shown at the top of the document if the loaded document contains an obsolete but convertible Parameters table study.
MNT-12133	B	It is not possible to launch an Indentation analysis on Force curve, Series of force curves and Force volume studiabes if the Spring constant is missing.
MNT-12150	B	The Wait cursor usually displayed during long calculations of the software is missing when the status bar is hidden.
MNT-12157	B	The coordinates of the Y-plane in the "3D view of the Hyperspectral image" study on Hyperspectral image studiabes are incorrect. The Y-axis is inverted.
MNT-12159	B	The terms Raman shift and Raman signal are always used in the table of the "Spectrum curve view", "Stacked view", "Strips view" and "Peak fitting" studies on Spectrum curve and Hyperspectral image studiabes as well as in the Select parameters dialog box, whether or not the data is Raman, rather than adapting to the name of the W axis as in the "Hyperspectral image view" study.
MNT-12166	B	The deactivation of the option Light interaction - Shadow effect in the "3D view of the surface" study on Surface studiabes is not preserved during the copy/paste operation.
MNT-12181	B	The Indentation points I0/Ip0 could sometimes be found outside of the working window during indentation analysis on Force curve and Force volume studiabes thereby affecting the numerical results calculated on these points.
MNT-12182	B	SmartFlows of more than one page are not added to the first available page of the document when applied.
MNT-12188	B	The dimensions of an addon study are lost when copying/pasting the study.
MNT-12195	B	It is no longer possible to specify the division size in the Axis settings of the "Summary of the current operator" study on Profile studiabes.
MNT-12215	B	Selecting a cell in the table of the "Particle analysis" study can change the order of the particles in the selected column on Surface and Image studiabes.
MNT-12230	B	The "Remote spikes" operator's instruction on Spectrum curve studiabes is too restrictive (the limitation on the maximum size of Spikes and Holese has been removed; the limit is the x-size of the area to be studied).
MNT-12247	B	The shortcut keys for scrolling through the "View of a hyperspectral image" study on Hyperspectral image studiabes are inconsistent with shortcut keys in other areas of the software.
MNT-12248	B	The specified offset on the Y-axis is inversed in 3D views on Shell studiabes when applying the "Convert to shell" operator.
MNT-12257	B	The modification of the deviation spacing in the "Advanced contour analysis" study on Profile studiabes does not work.
MNT-12258	B	The modification of the deviation margins is no longer applied on both sides of the profile in the "Advanced contour analysis" study on Profile studiabes.
MNT-12264	B	The application of the Average the profile option in the "Extract profiles" operator dialog box is different for oblique profiles to that of horizontal or vertical profiles on Surface, Image, Surface + image, Multi-channel image, Hyperspectral image and IV spectroscopy image studiabes.
MNT-12269	B	The Rzx parameter of ISO 21920-2 on Profile studiabes is not calculated correctly.
MNT-12313	B	It is not possible to modify the reference frame for alignment of several frames.
MNT-12319	B	The manual cut-offs are not correctly taken into account when applying the "Metrological filter" operator.
MNT-12337	B	Some "Move" actions in documents created in V7 (or previous) are not applied in the Advanced contour analysis study on Profile studiabes when the document is loaded in the current version.
MNT-12369	B	Several visualizations or functions are not available in the Source view of the "Extract surface" operator on Shell studiabes.

MNT-12419		The display of vertical Profile studiabes is not correctly centered in the "Load a studiabile" dialog.
MNT-12462	B	The frames become misaligned with the calculation area and distort as the zoom moves in the "Valley depth measurement" study on Surface and Multi-channel image studiabes.
MNT-12462		The error message is missing from the Advanced contour study on profile studiabes if a DXF is loaded that contains only elements which are not supported by the software.
MNT-12569		It is not possible to create a result using the Results calculator if the results to be used are based solely on constants or on the Rnd function if it returns a value of less than 1, but greater than or equal to zero.

## What's new

	Transparent forms in 3D views of operators
Transparency in 3D preview of operator dialogs	In the dialog box of several operators on Surfaces, it is now possible to display some previews in 3D. The source studiable is then displayed together with transparent layers, to bring an informative visualization about the operator settings (for example, threshold planes in the "Threshold" operator). This applies to the operators: "Threshold", "Level", "Remove form", "Metrological filter", on Surface, Surface + Image, Series of surfaces and Multi-channel image studiabiles. More information for each of them below.
Transparent thresholding plane in the "Threshold" operator	The "Threshold" operator dialog preview can display the source studiable in 3D with its transparent thresholding planes.
Transparent leveling plane in the "Level" operator	The "Level" operator dialog preview can display the source studiable in 3D with its transparent levelling plane. For minimum zone method, the two parallel enclosing planes are displayed.
Transparent fitted form in the "Remove form" operator	The "Remove form" operator dialog preview can display the source studiable in 3D with its transparent fitted form. The "Remove form" operator dialog has also been reorganized.
Transparent waviness in the "Metrological filter" operator	The "Metrological Filter" operator dialog preview can display the source studiable in 3D with its transparent waviness form.
Settings for 3D in dialog preview	Buttons above the preview allow to switch between 3D or Pseudo-color visualization. In 3D visualization, the result studiable preview is also in 3D, and a change in choice of 2D/3D above one preview window is dynamically applied to the other. The last-used preview visualization is remembered for the following opening of the dialog.
	Transparent forms in Summary of the current operator
Transparent 3D forms in the "Summary of the current operator" study	In the "Summary of the current operator" study, for some operators, the 3D view now displays the same transparent forms as the ones in the operator's previews. This applies to the same 4 operators listed above: "Threshold", "Level", "Remove form" and "Metrological filter" on Surface, Surface + Image, Series of surfaces and Multi-channel image studiabiles.
3D view by default in the "Summary of the current operator" study	For the 4 operators listed above, 3D visualization is now the default visualization mode in the "Summary of the current operator" study.
3D setting buttons in the "Summary of the current operator" study	3D rendering and accessories buttons have been added to the ribbon of the "Summary of the current operator" study in 3D mode (if available). On Surface + image and Multi-channel image studiabiles, channel buttons are also available to select texture.
	Feret parameters and unit choices in the "Particle analysis" study
Feret parameters in the "Particle analysis" study	The Min Feret diameter and the Perpendicular Feret diameter (xLF) have been added in the "Particle analysis" study parameters. The Max caliber parameter has been renamed Max Feret diameter.
Unit of particle density and area in the "Particle Analysis" study	The user can now fix particle density units (by nm <sup>2</sup> , μm <sup>2</sup> , mm <sup>2</sup> , cm <sup>2</sup> ) in the "Particle Analysis" study. The "Density (in Pixels)" (in Particle/pixel <sup>2</sup> unit) and "Area (in Pixels)" (in pixel <sup>2</sup> unit) are now available.
Palette color mapped to Z scale height in the "Threshold" operator	In the "Threshold" operator dialog, the color palette on the right is positioned so that the color corresponds to the height of the Z scale. It applies to the Surface, Image, Surface + image and Multichannel image studiabiles

	<a href="#">Cursor on W axis of spectrum</a>
Cursor on the W axis of spectrum	The user can move a cursor (vertical dotted line) along the W axis of Spectrum curves. This allows the user to display the values of the W position and spectrum intensity in the information parameters. It is available for all studies on Hyperspectral image and Spectrum curve studiabes (it was previously only available on some studies for Hyperspectral images). This cursor can be synchronized among several studies (all the synchronized cursors move together)
	<a href="#">Scrolling across spectral data</a>
Slices image scrolling	In the Cinema mode of the "View of a Hyperspectral image" study, the scrolling speed of the images of the slices has been optimized.
Visualization of current spectrum	In Optimize for current curve mode, the Z-range is adapted when scrolling among the spectra. It is now available for all studies showing Spectrum curves (it was previously only available on the "View of a Hyperspectral image" study).
Keyboard shortcuts	In all studies showing Spectrum curves, you can now scroll across the spectra using the same keyboard shortcuts. Modified shortcuts allow the user to skip non-measured spectra.
	<a href="#">Other improvements in Spectral studies</a>
Curve position in the "Strips view" study	The vertical axis of the "Strips view" study now allows you to display either the spectrum curve number, or the curve position (included in the T axis). It applies to Hyperspectral image, Spectrum curve, IV spectroscopy image and IV curve studiabes.
Normalize view in all studies	A [Normalize] button is now available on all studies displaying Spectrum curves. The "Normalize" study is now obsolete and is no longer available from the ribbon. When opening documents created with a previous version, the study is replaced by a "Spectrum curve view" study with normalization activated.
Interface adjustment in Spectrum curve view and Peak fitting	The interface to choose curves to display (envelope, mean etc.) has been simplified and homogenized with the "View of a hyperspectral image" study. Another little ribbon simplification has been made. It applies to "Spectrum curve view" and "Peak Fitting" studies on Spectrum curve and Hyperspectral image studiabes.
	<a href="#">Other</a>
Composite rendering and slider behavior	In the studies, when Composite rendering is activated, the user can no longer select a channel which is not included in the composition. The Comparison slider has a similar behavior, for better understanding.
Crop points outside range in 3D	In 3D view study, the Crop points outside imposed scale range option is now placed in the [3D shape] sub-menu.
Updates for Installation guide	The technical specifications of the Installation guide have been updated.

## Bug corrections (A and B type)

	Type	Bug Description
MNT-11862	A	The software may crash when loading a TXT file if the Show a dialog box when loading a text file option is not checked in the Loading data/Text file format section of Global Preferences.
MNT-11975	A	The software may crash when clicking on one of the Extraction shapes f(Radial or Double parallel extraction shapes), selecting the Average the profile option and then entering the Half Width value in the "Extract local contour" operator on Surface studiabes.
MNT-11980	A	The calculation of the Average the profile option in the "Extract profiles" operator is not correct in the "Step height calculations" study on Surface, Surface + image, Multi-channel image studiabes.
MNT-12023	A	The software may crash when a document containing a 3D view study using an uninstalled font is opened.
MNT-12026	A	Some fonts do not work in 3D view studies and could cause the application to crash.

MNT-12033	A	The software may crash in the "3D reconstruction using four quadrant images" operator on Image studiables when the reconstruction method 'Optimize for objects on a flat background' is selected and the threshold slider is moved.
MNT-12043	A	The Peak position values (P1, P2...) in the result's table of the "Peak fitting" study on Spectrum curve and Hyperspectral image studiables do not respect the order of the peak positions on the study graph.
MNT-12146	B	The software may crash when opening the "Enhance" operator dialog box on Image studiables
MNT-11831	B	Studies on the page of the document may be incorrectly placed with regards to elements on the page background.
MNT-11845	B	Some parameters of the "Peak fitting" study (Initial time (t0), Time constant 1 (tau1) and Time constant 3 (tau2)) are not expressed in the correct unit in the study's results table.
MNT-11846	B	The Area normalization method in the "Normalize" operator on Spectrum curve and Hyperspectral image studiables can show negative/inverted spectrum curves. This also applies to the Normalize option in the "Spectrum curve view" and "View of a hyperspectral image" studies.
MNT-11859	B	The names of the F-operators applied to addon parameters on Profile studiables are incorrect.
MNT-11861	B	Parameters are deselected in the 'Tolerance limits' manager dialog box every time the tolerance is modified.
MNT-11864	B	The software may crash when creating a "3D view of the surface" study on Surface studiables if default settings have been saved in version 11.0.11118.
MNT-11865	B	The addon update dialog, when requested from outside Mountains®, is not closed when the Yes button is used.
MNT-11886	B	The Surface + image studiable resulting from the application of the "3D reconstruction using four quadrant images" operator on Image studiables does not have two distinct top and bottom parts if the reconstruction method 'Optimize for two-level crenels separated by a step of' of the 'Default algorithm (recommended)' choice is selected.
MNT-11893	B	A hypertext link is not correctly created and does not work when exporting the numerical results of a document to a text file in CSV format if the text file name contains spaces.
MNT-11907	B	Results in an "Advanced contour analysis" study on a Profile studiable may not be calculated in some rare cases if the original document was created in a very old version of the software in Japanese language and there are a large number of dependencies in the study.
MNT-11909	B	The "Advanced contour analysis" study on Contour profile studiables can be very slow to load and open for studies with thousands of elements with many dependencies.
MNT-11919	B	It is not possible to navigate in the series in the Source preview of the "Extract areas" operator dialog box on Series of surfaces and Series of images studiables.
MNT-11926	B	The Hide checkbox disappears in the Add RGB in the background image dialog box of the "Colocalization" study on Surface and Image studiables when resizing the dialog box
MNT-11937	B	An isolated point in a "Profile" studiable is not present in the result when applying the "Level" operator if the Minimum zone line (MZLI) option is selected in a particular case.
MNT-11953	B	Image studiables having 16/24/32 bits per channel are not always loaded with their full resolution.
MNT-11961	B	Synchronization between the source view and the result view in operators on Shell studiables is lost ("Extract area", "Extract projected surface", "Extract contour profile", "Fill in holes", "Metrological filter" and "Fit a geometric form" operators).
MNT-11976	B	Multiple instances of Mountains® (rather than multiple tabs) may be launched when loading several documents from the file explorer in some configurations.
MNT-11981	B	The saving of the settings of the Min/Max value of the Imposed scale option is not preserved in the Scale range section of the Settings for Z-axis on Surface studiables.
MNT-12057	B	The "Table of results" study is not always updated after the modification of the numerical results generated by an operator using MATLAB™.
MNT-12062	B	The parameters of the "Peak fitting" study are not displayed in the study's result table or in the Result manager.
MNT-12077	B	Mouse selection of the bars that define the fitting zones is difficult in the "Peak fitting" study on Hyperspectral image and Spectrum curve studiables.
MNT-12082	B	Selecting the Spectral Curve (W) attribute in the synchronization manager on spectral studies for W axis synchronization is lost after saving and reopening the document.
MNT-12088	B	The magnetic grid is only displayed on the first page of the document if documents' margins are displayed.

MNT-12116	B	Loading a document containing an unknown study or addon operator generates an error message (instead of loading the document and displaying warnings for studies and operators that could not be loaded).
MNT-12149	B	The "Table of results" study does not display results generated using the Result calculator if the document has been saved in version 10.0.

## What's new

	<b>Homogenization of Spectral studies</b>
Normalized display in Spectral studies	A normalized display is now available on most studies on Hyperspectral image and Spectrum curve studiabiles. The [Normalize] button has been added to the "Spectrum curve view", "Strips view" and "Stacked view" studies.
Cursor on spectrum axis in "Spectrum curve view" study	A movable cursor is now displayed in the "Spectrum curve view" study. It is possible to display the corresponding abscissa (W) and ordinates (Z) of the current spectrum in the study's results table (by selecting them from the Information tab of the Select parameters dialog).
Simplified Spectrum curve parameter	The Spectrum curve parameter now only displays the current curve element number. (Coordinates in pixel have been removed). This concerns all studies on Hyperspectral image studiabiles (except 3D).
Statistical parameters removed in Spectral studies	The statistical parameters have been removed from the "Spectrum curve view" study and the "Peak fitting" study. A message informs the user when loading documents created in previous versions of the software. It is still possible to create statistical studies from series of results, coming from the "Spectrum curve view" study or "Peak fitting" study.
Skip empty curves in Spectral studies	When navigating through spectra, the user can now skip the pixels with empty curves (non-measured points) using Ctrl+Page up/Page down shortcut. This concerns all studies on Hyperspectral image and Spectrum curve studiabiles.
Shortcut to navigate between slices of Hyperspectral images	In the "View of a hyperspectral image" study, the user can now navigate between slices (W spectral axis) using the Shift+ Page up/Page down shortcut.
Homogenization of spectrum curve style interface	The ribbon buttons for curve visualization and style, have been homogenized with Hyperspectral image study interface. This applies to "Spectrum curve view" and "Peak Fitting" studies on Hyperspectral image and Spectrum curve studiabiles.
[Analysis] group on spectral studies ribbon	The [Peak fitting] button in the Studies tab on Spectral studiabiles has been moved to a new [Analysis] group.
	<b>Removal of non-applicable preferences</b>
Removal of non-applicable preferences	The Global Preferences of the software are now displayed only if applicable on user product. This concerns the following preferences: <ul style="list-style-type: none"> <li>. The 3D preferences and the Spectral Axis Orientation in the Axis settings section.</li> <li>. The Create Multi-channel image function in the Other actions section.</li> <li>. The Types of studies in the Default studies, Exporting studiabiles and Default Smartflow sections.</li> <li>. Show Cloud point studiabiles in the in the Default Smartflow, Default studies, Exporting studiabiles sections.</li> </ul>
	<b>Other general features</b>
Reduced calculation time in the "Stitch together in 3D space" operator	The calculation time has been improved in the "Stitch together in 3D space" operator on Point cloud and Surface studiabiles.
Increased cinema speed on Hyperspectral images	The speed showing slices along the spectral axis (W-axis) using an animation has been improved on Hyperspectral image studiabiles. The rendering has been also optimized when scrolling through the slices. This also applies to IV spectroscopy image studiabiles.
Information on obsolete 3D view on Multi-channel cubes	A message now suggests using the new "3D view of the cube" study on Multi-channel cube studiabiles, where applicable, when reloading documents created in previous versions.

Link to direct print	The user can create a button or a hyperlink in the document, that directly prints the document without any dialog. It replicates the last-used printer settings.
Studiablist in operator dialogs	The list of selectable studiablist in the following operator (or study) dialogs, now display an improved and homogeneous interface: "Create series of surfaces", "Create series of profiles", "Create multi-channel image", "Create series of force curves", "Create series of images", "Add/remove surfaces", "Add/remove profiles", "Add/remove channels", "Add/remove overlay", "Add/remove force curves", "Add/remove images", "Add/remove spectrum curves", and "Patch".
PDF export on command	It is now possible to export the current document as a PDF using a simple command line (name and path is no longer required).

## Bug corrections (A and B type)

	Type	Bug Description
MNT-10985	A	The software may crash when calculating parameters on deviations on Shell studiablist if they contain infinite values.
MNT-11463	A	Curves inserted in the result of the "Add/remove spectrum curves" operator on Spectrum curve studiablist may be lost when recalling or recalculating the operator if the added curves are no longer available (deactivation of the operator that applies to the added curves).
MNT-11584	A	The 3D view of the "Summary of the current operator" study is not updated properly in some cases during studiablist substitution.
MNT-11663	A	The calculation may take a long time or the software may crash when applying certain combinations of operations from the Alignment and Post-processing sections in the "Stitch together in 3D space" operator on Shell studiablist.
MNT-11709	A	The software may crash when loading old documents containing a "Summary of the current operator" study on Shell or Point cloud studiablist.
MNT-11733	A	The software may crash when exporting the "Summary of the current operator" study on Multi-channel image studiablist as an image.
MNT-11754	A	The unit is incorrect by default when first launching the software and when restoring factory settings in the "Extract areas" operator. Affects all studiablist types.
MNT-10302	A	Rendering colors are not preserved in the "CAD compare" study on Shell studiablist when reloading a document in a particular case.
MNT-11778	A	The software may crash when loading a document containing studies with synchronized cursors in a particular case.
MNT-10286	B	The "Extract contour profile" operator on Shell studiablist never generates a closed contour profile, and the 'Create circle (from closed profile)' tool in the "Advanced contour analysis" study on Profile and Contour profile studiablist therefore cannot be applied.
MNT-11431	B	The color scale is not shown in the 3D view of a "Thickness analysis" study when loading documents where this was visible if they were created in previous versions of the software.
MNT-11494	B	It is not possible to optimize the palette of the reconstructed tip in the 3D view Tip surface of the "Tip deconvolution" operator.
MNT-11524	B	The spacing between the contour lines is incorrect in the "3D view of the surface" study if the Imposed scale option in the Scale range section of the Z-axis settings is selected.
MNT-11537	B	The display of the curvature in the Color options in the "3D view of the shell" study on Shell studiablist is not reapplied when reloading documents created in previous versions of the software.
MNT-11550	B	The normalization mode in the X/Y-axis settings in the "3D view of the multi-channel image" study on Multi-channel image studiablist is not recovered when reloading old documents.
MNT-11555	B	The filling is incorrect in the "Morphological envelopes" study on Profile studiablist.
MNT-11560	B	Only the maximum amplification is visible in the 3D view of the "Thickness Analysis" study. The studiablist are displayed without their actual position in the "Wear or Deposit" study.
MNT-11572	B	The topography and intensity layers share the same palette in the "3D view of the surface + image" study on Surface + image studiablist.

MNT-11573	B	The 3D view result disappears in the “Map local properties” operator when displaying the intensity layer of a Surface + image studiable.
MNT-11574	B	It is not possible to change the Source view channel in the “Map local properties” operator on Surface + image studiabiles.
MNT-11576	B	The order of studiabiles in the Available studiabiles list in the “Stitch together in 3D space” operator on Surface studiabiles is incorrect when recalling the operator.
MNT-11579	B	Undo/redo of the application of the options of the [3D shape] button in the 3D view studies does not work.
MNT-11601	B	Updating from some builds in version 10 to version 11 via the Download new major version button in the Search for updates function in the Help tab can result in downloading an incomplete or unusable file.
MNT-11602	B	Graduation displays are sometimes incorrect in the 3D view of studies.
MNT-11613	B	The number of points shown in the visualization of the Resolution under the [3D shape] button is incorrect in the “3D view of the surface” study on Surface studiabiles.
MNT-11614	B	The Optimize setting in the Resolution option in the [3D shape] button of a 3D view study is not applied by default when creating a studiable of higher resolution than the current 3D preferences. Affects Surface, Image, Series of surfaces, Surface + image, Multi-channel image, Multi-channel cube, Shell, Hyperspectral image, IV spectroscopy image studiabiles.
MNT-11615	B	The Optimize feature from the [Resolution] button in the “3D view of the surface” study is not taken into account when reloading documents created in previous versions of the software.
MNT-11639	B	The 3D view of the “Wear or Deposit” study on Surface studiabiles is displayed outside the frame if the option A single thickness layer is selected in the Selection of analyzed layers dialog box.
MNT-11646	B	Modifications to the Object colors and 3D print options are not taken into account in the preview of the Export options for the 3MF file format on Surface + image studiabiles.
MNT-11650	B	The validity of tolerances is not always correctly updated in the “Table of results” study when a result used in the Define tolerance limits dialog box is modified.
MNT-11652	B	It is not possible to colorize the mesh using curvature in the “3D view of the shell” study on Shell studiabiles after applying the “Correct the shell” operator.
MNT-11659	B	The extraction area in the “Extract areas” operator on Shell or Point cloud studiabiles is shifted when recalling the operator.
MNT-11665	B	Editing a constant in the Result calculator renames the constant rather than updating it.
MNT-11700	B	The width of the averaging area is not preserved when loading a document containing the “Extract profiles” operator on Surface studiabiles if the document was created in version 9.
MNT-11712	B	The display of the curvature in the Color options in the 3D view study on Shell studiabiles is incorrect after copying and then pasting the frame.
MNT-11713	B	The rendering in the “3D view of the shell” study on Shell studiabiles is not saved when using the Save settings option of the [Save/apply settings] button.
MNT-11732	B	The Z-axis settings of the 3D view of the “Wear or deposit” study are not taken into account and the Color scale is not modified when the Imposed scale option of the Scale range section is selected in the Settings for the Z-axis under the [Axis settings] button.
MNT-11755	B	The deviations displayed in the Mesh + deviation view of the “Fit a geometric form” operator on Shell studiabiles do not always correspond to the current shape selected.
MNT-11775	B	Applying the Deviations setting as a 3D rendering on Shell studiabiles is lost when saving and reloading the document.
MNT-11803	B	The “Correct the baseline” operator does not properly correct all spectrum curve studiabiles when selecting the Set average selection to 0 option in the Settings section in a particular case.

## What's new

### GENERAL FEATURES FOR ALL PRODUCTS

- COPY/PASTE PART OF THE WORKFLOW
- EXPORT PDF IN BATCHES – MERGE DOCUMENTS
- NAVIGATION BOX
- EASY POSITIONING OF FRAMES IN DOCUMENT
- NEW “DOCUMENT” AND “ILLUSTRATIONS” TABS
- PRODUCT LEVEL CHOICE
- HOME SCREENS
- OTHER GENERAL FEATURES

### MULTI-TECHNOLOGY FEATURES

- MORE REALISM IN 3D RENDERING
- 3D VIEW STUDY’S RIBBON
- X - Y CURSOR ON SURFACES AND IMAGES
- STITCHING OPERATOR
- NEW “EXTRACT LOCAL CONTOUR” OPERATOR ON SURFACE AND ON IMAGE
- CORRELATION IN “SCALE SENSITIVE FRACTAL ANALYSIS” (SSFA) STUDY ON SERIES
- CLASSIFICATION IN “FIBER ANALYSIS” STUDY
- EDGE PRESERVING FILTERS
- CUBE CUTTING PLANES
- ADAPTATION OF TOOLS TO MORE STUDIABLE TYPES
- LINKED STUDIES

### PROFILOMETRY FEATURES

- SHELL AND POINT CLOUD FEATURES

### SPECTROSCOPY FEATURES (FOR SPECTROSCOPISTS OR SPM USERS)

### NEW MOUNTAINS® PRODUCTS

### UPDATES AND TRANSLATIONS FOR INTERFACE & REFERENCE GUIDE

	<b>General features for all products</b>
	<b>Copy/paste part of the workflow</b>
Application of a part of the workflow on another studiable	The user can apply a part of the document workflow (operators and studies) on another studiable, using Copy/Paste. The studiable can be in the same document or in another document. This can be considered as a temporary SmartFlow (with only one root studiable).
Extraction of a part of the workflow in another document.	Users can now copy a part of the document workflow, and paste it in another document (or in the same document). For example, this allows you to extract studiabes, their treatment (operators) and analysis (studies), without upstream pre-processing, or coming from an overloaded document.

Modification of the studiable on which a branch of the workflow is applied	It is now possible to modify the studiable on which a branch of the workflow is applied. Using drag and drop in the workflow, a branch can be moved to another studiable of the same document, without modifying the position of the studies in the document. This allows the user to rapidly visualize the application of the current analysis on another studiable.
	<a href="#">Export PDF in batches – Merge documents</a>
Batch export of several documents to PDF, RTF, print	It is now possible to export several Mountains® documents at once in PDF or RTF format. The user can choose the file names and the export folder location. PDF format allows sharing with any user, whereas RFT format allows insertion in a document editor software. Selected documents can also be batch printed.
Merge of Mountains® documents	It is also possible to merge several Mountains® document into a single PDF or RTF document. The user can choose the order of the documents to be merged.
Access to the Batch export dialog	The Batch export dialog is available from the Document tab, from the File tab, and from the contextual menu of the Mountains® File explorer panel.
	<a href="#">Navigation box</a>
Navigation box in studies	A navigation box is now temporary displayed when zooming in image views on studies. It shows the position of the zoomed zone in real time on the full zone. The zoom zone position can be modified on the fly using the mouse. This Navigation box is also displayed when zooming in operator previews. The navigation box is available for Surface, Surface + images, Multi-channel image, Series of surfaces, Series of images, Force volume, Hyperspectral image, IV spectroscopy studiables.
	<a href="#">Easy positioning of frames in document</a>
Visual indicators for alignment	When moving frames in the document, temporary visual indicators are now visible, and magnetism can be used to facilitate alignment with other frames.
Frame alignments	The position of two (or more) frames can be horizontally or vertically aligned on their borders or their centers. It is also possible to align several frames on the center (or borders) of the page.
Vertical or horizontal frame distribution	The position of three (or more) frames can be distributed to get the same horizontal or vertical distance between neighboring frames.
Properties dialog in multi-selection	The frame Properties dialog is now available when selecting several frames. In particular, it allows you to change the size of several frames at once.
Moving frames with directional keys	The keyboard directional arrows now move the frame position. Shift+arrow moves the position of the zoomed portion in the study, and Ctrl+arrow moves the cursor if any.
	<a href="#">New “Document” and “Illustrations” tabs</a>
Document tab	The Edit tab has been renamed “Document” and reorganized. The Document tab displays editing functions related to the format and layout of the current document. It also contains export functions.
New “Illustrations” tab	The illustrations frames, previously included in the Edit tab, are more directly accessible in a new “Illustration” tab. Shapes and Arrows illustration settings are directly available from ribbon’s buttons. The Illustrations tab contains frames useful for commenting on your analysis, or to give instructions (text, circle, image, etc.), to ensure traceability (date, username, document path, etc.), to enable navigation (hyperlinks between documents or to a website, etc.) or to facilitate the use of the document (action button for operator recall, document saving, etc.).
View tab	The View tab has been reorganized. It displays functions to personalize the workspace, define frame positioning and change the Zoom.
Page viewer panel display	The Page viewer panel now appears when first opening Mountains or when restoring factory settings. When updating or reinstalling Mountains, the Page viewer panel follows the previous user choice as set in the View tab.
	<a href="#">Product level choice</a>
Compatibility between document and product level	The software now evaluates compatibility between the current document and the products in the range. The user thus benefits from assistance to choose the necessary product level when purchasing or upgrading (see below).
Incompatible document	When the current document is not fully compatible with the current product level, the user can open the Compatibility dialog from an information strip at the top of the document locally. This dialog displays the list of product levels (product name and necessary modules) authorizing all the functions contained in the current document. The user can copy the name of the product levels into the clipboard.

Incompatible study or operator	When the document contains a feature not available in the current product level (study, operator), the user can open the Compatibility dialog from the contextual menu of the corresponding line in the Workflow panel. In this case, the Compatibility dialog displays the list of product level compatible with this particular feature.
Switch to compatible product	Using a Free trial, OEM demo or Loan license, the dialogs allow the user to switch to a compatible product.
Compatibility dialog access	Even if the current document is fully compatible, the Compatibility dialog can be displayed, from the Help tab, License dialog.
	<a href="#">Home screens</a>
Shortcut and Splash screen	The Shortcut icon and the Splash screen have been redesigned.
Home and Learning tabs in the Home dialog	The Home dialog page has been refined and now has two sections for greater readability. The Learning section allows the user to discover Mountains® using various resources. The Home section invites the user to start working (new document or studiable, recent document or studiable), and to discover new version features.
Blue gradient color theme	Mountains® 11 introduces a customized modern “Blue gradient” screen theme, set by default. The “Blue gradient” color is a gradient from dark blue to lighter blue, with touches of “jungle green”.
	<a href="#">Other general features</a>
Operator recall button creation	You can rapidly insert a button to recall an operator from the operator line in the Workflow panel.
Vertical text in Screen notes and bubbles	The text can be positioned vertically in the Screen notes and Bubbles illustrations.
Color of tables with results in studies	All tables listing parameters or results in studies now use the same light green as in the “Parameters Table” study, for greater consistency. This applies to all studies generating results, and to the “Table of results” study.
Shortcuts to Tolerance limits from the “Table of results” study	You can open the Tolerance limits dialog by double-click on the Pass/Fail or Tolerance column of the “Table of results” study. If a line or a cell was previously selected, the corresponding parameter will be selected in the Tolerance limits dialog. The corresponding parameters are also directly selected in the ‘Tolerance limits’ manager dialog, when you select one or several lines in the “Table of results” study, and you click on the [‘Tolerance limits’ manager] button.
Saving multiple studiabilities	The saving of several studiabilities at the same time is now possible from the contextual menu on a multi-selection of studiabilities in the workflow.
Link to license details from About dialog	A Show license dialog box link is displayed in the About dialog, to rapidly access more details about the license.
Default data display in Global Preferences renamed	The Loading data / Default SmartFlows preference, and the Data display / Default studies preference have been renamed and reorganized for better clarity.
Read only text in the file name	[Read only] text is displayed at the top of the software window after the file name, if the file has a “Read only” attribute. The information strip at the top of the document is no longer displayed.
[Assemble] ribbon group reorganized	The [Assemble] group of the operator ribbon has been splitted into three groups: [Assemble], [Add/Delete] and [Create]. These groups are or are not, visible depending on the operators available for the studiabilities.
Loading studiabilities in all products	All studiable types can now be loaded into all products (provided that the file format is included in the product). Only the “Identity card” study can be displayed. For some studiable types (e.g., surface-image), extraction operators have been added in relevant products. In the File explorer panel, the icons of all studiable types (of file formats included in the product) can be visualized.
Distinguishing RGB images from grayscale images in the name	The distinction between RGB and grayscale images has been added to the name of the studiable type displayed in the workflow, as is done in the identity card. “Grayscale image” or “RGB image” is displayed when hovering over the icon.
Enhanced integration of Mountains® from external applications	It is now possible to get a separate Mountains® application window when driving Mountains using ActiveX from an external application (it was previously only possible to integrate Mountains interface inside the external application window). It is also possible to drive several Mountains windows. The applications run separately, preventing one application from crashing even if it crashes in another window.  The Software Development Kit documentation has been updated (available from the Automation tab).

	<h2>Multi-technology features</h2>
	<h3>More realism in 3D rendering</h3>
3D rendering engine more realistic	All studies and operators using 3D rendering with light effect, now benefit from a physically based rendering, resulting in a more realistic display. It concerns the 3D view study on Surface, Series of surface, Surface + image, Image, Multi-channel image, Multi-channel cube, Shell, Cloud of points, Hyperspectral image and IV spectroscopy image studiabilities, the “Wear and deposit analysis” study on Surface, Series of surfaces, Surface + image and Multi-channel image studiabilities, and the 3D previews in the operators “Single-image reconstruction”, “Stereoscopic reconstruction”, “3D reconstruction using three images”, “3D reconstruction using four quadrant images”.
Improved graduation display	The graduation texts are sharper and with less overlap.
Intuitive rotation in 3D renderings	The center of the rotation is now the center of the zoomed zone (and not the center of the surface) in 3D view renderings.
	<h3>3D view study’s ribbon</h3>
Material settings in 3D view study	Roughness and metalness visual aspects can now be defined (using sliders), on all renderings using light. It replaces the previous Gloss setting.
Lines on top of rendering in 3D view study	The lines can now be displayed on top of any rendering (lines, mesh, contour lines).
3D view ribbon reorganization	The ribbon of the 3D view studies has been reorganized for more intuitive settings.
Slider for amplification in 3D view study	A slider can now be used to set the z amplification.
Modernized icons in 3D view study	Some icons of the 3D view study have been modernized.
	<h3>X - Y cursor on surfaces and images</h3>
X-Y cursor on surfaces and images	A cursor can now be displayed in some studies on Surface, Image and comparable studiabilities. The cursor shows two perpendicular crossed dotted lines. The studies with cursor can display X and Y position values (in the current coordinate system, relative or absolute) and the Z value if applicable (in the current Z scale) of the current surface element in the study’s table. In automation context, the X-Y cursor position is defined in absolute coordinate values. This applies to “Pseudo-color view” and “Summary of the current operator” studies on Surface, Series of surfaces, Images, Surface + Image, Multi-channel images and Multi-channel cube studiabilities, to “Photo simulation” and “Contour lines” studies on Surface studiabilities, and to the “True color view” study on Image and Series of images studiabilities. The values are not included in the result manager.
	<h3>Stitching operator</h3>
“Stitch” operator redesigned	The “Stitch” operator dialog has been completely redesigned for better ergonomics, allowing for covering a greater number of cases, and expanded automation possibilities (see below).
Big preview in “Stitch” operator	The grid view (showing the position of each studiable in its corresponding tile), is displayed in a big preview. The user can switch between the grid view and the result preview.
Semi-automatic method in “Stitch” operator	The manual positioning has been replaced by a semi-automatic setting called Use studiable properties. This method uses rules to position the studiabilities in the grid view, using starting position on a corner, filling path, and sorting rule (from studiable name, measurement date or studiable number in the workflow). It also allows the user to define a global overlap between tiles. Manual refinement of the position of a tile is possible, with transparency effects and optional magnetism between tiles. The completely automatic methods (‘Use XY absolute coordinates’ and ‘Use automatic feature detection’) have been renamed but not modified.
Easy and automatable selection of studiabilities in “Stitch” operator	A searching bar can be used in the “Stitch” operator, either to temporarily help the user to find and select a compatible studiable, or to define studiable selection rules applicable in automation contexts (for example, to select all surfaces after micro-roughness filtering, regardless of the number of surfaces in the document). The reference studiable is identified in bold text.
	<h3>New “Extract local contour” operator on surface and on image</h3>
New “Extract local contour” operator on Surface and Image	The new “Extract local contour” operator locally detects edges and generates a Contour profile from Surface, Surface + image and Image studiabilities. The edge detection method is applied on extracted auxiliary profiles.

Extraction shapes in “Extract local contour” operator on surface and image	The user can select and position different profile extraction shapes (parallel, double parallel, and radial). The number of profiles (extraction resolution) and optional average width can be defined.
Edge detection methods in “Extract local contour” operator on Surfaces and Images	The edge detection applied on the extracted profiles uses either Threshold, Derivative, or a Polynomial method. The user can choose to detect only rising, only falling edges, both rising and falling, or the average. For the derivative method, it is possible to set the searching window size, to smooth the derivative, and to fine tune the detection sensitivity.
	<a href="#">Correlation in “Scale sensitive fractal analysis” (SSFA) study on Series</a>
Scale of better correlation between T axis and developed length in SSFA study on Series	In the “Scale sensitive fractal analysis” study, it is now possible to evaluate the correlation between a variable T along a Series (entered by the user), and the developed profile length (or developed surface area) at a defined scale. You can display the Regression coefficient R <sup>2</sup> coefficient along the series in function of the scale. The maximum of this graph gives the scale at which there is the better linear correlation between developed length (or area) and a variable. It allows the user to find at which scale a variable has an effect on the surface. The variable can be a value of the fabrication process (e.g., polishing speed) or a functional property (e.g., tribological behavior). This applies to Series of profiles and Series of surface studiabiles.
Statistical studies on SSFA study for Series	It is now possible to apply statistical studies (“Control Chart”, “Scatter plot”...) on the results of the “Scale sensitive fractal analysis” (SSFA) study on Series of profiles and Series of surfaces studiabiles.
	<a href="#">Classification in “Fiber analysis” study</a>
Classification in “Fiber analysis” study	It is now possible to classify the fibers in the “Fiber analysis” study. The classification functions are identical to the ones in the “Particle analysis” study. In particular, you can classify the fibers using parameters values or a combination of parameters values, exclude classes from calculation, display color by class and legend, calculate statistical parameters by class, and share classifications on other documents or with colleagues. The “Fiber analysis” study is available for Image studiabiles (in particular SEM images), and for Surface-type studiabiles.
Histogram display in “Fiber analysis” study	It is now possible to hide the histogram or to change its color in the “Fiber analysis” study.
Dynamic images from “Fiber analysis” study	Dynamic image export is now available for all images produced by the “Fiber analysis” study on surfaces or on SEM images.
	<a href="#">Edge preserving filters</a>
Edge preserving filters in “Spatial filter” operator	The ‘Bilateral’ filter and the ‘Guided’ filter have been added in the “Spatial filter” operator. Those filters reduce noise while preserving the edges. Sliders are available to find the best compromise between noise reduction and edge preserving. This also applies to Image, Series of images, Surface, Surface + image, Series of surfaces, Multi-channel image, Multi-channel cube studiabiles.
	<a href="#">Cube cutting planes</a>
XY cutting planes in Multi-channel cubes	Cutting plane in X or Y direction can now be displayed in the “Pseudo-color view” study on Multi-channel cube studiabiles (previously only Z was displayed).
	<a href="#">Adaptation of tools to more studiabile types</a>
Availability of operators or studies on Surface + Images	The “Fit an asphere” operator, and the “Volume parameters”, “Sk parameters” and “Slope distribution” studies are now available for Surface + image studiabiles.
Availability of operators on Series of surfaces	The “High/Low pass filter”, “Morphological filter” and “Edit axes” operators are now available for Series of surfaces studiabiles.
Availability of operators on Series of images	The “Rotate”, “Enhance the image”, “Homogenize lighting”, “High/Low-pass filter”, “Convert to series of surfaces” and “Convert RGB to monochrome image” operators are now available for Series of images studiabiles.
Availability of operators on Series of profiles	The “Morphological filter” operator is now available for Series of profiles studiabiles.
	<a href="#">Linked studies</a>
Synchronization between studies	It is now possible to link the attributes of several studies of the same document (synchronization). It means that if several studies are synchronized using a link concerning an attribute, the modification of this attribute in one of the studies, modifies this attribute in all other linked studies accordingly. See below the attributes that can be linked.

XY-position synchronization	<p>The position of the X-Y cursors can be linked between studies.</p> <p>X-Y cursors positions are defined in absolute coordinate's values. Error cases (for example cursor position outside of the study's border) are managed with informative error messages.</p> <p>This applies to the "Pseudo-color view" study and to the "Summary of the current operator" study on Surface, Series of surfaces, Images, Surface + Image, Multi-channel images and Multi-channel cube studiabiles, to "Photo simulation" and "Contour lines" studies on Surface studiabiles, and to "True color view" study on Image and Series of images studiabiles.</p> <p>This X-Y position can also be linked with studies on Hyperspectral images studiabiles (and on IV images studiabiles). It concerns cursor positions in the "View of a hyperspectral image" and "View of an IV spectroscopy image" studies and displayed curve for the other studies ("Spectrum curve view", "Peak fitting view", "Normalized view", "Stacked view", "Strips view").</p>
Zoom in % (XY) synchronization	<p>The image zoom level (in %) can be linked between studies.</p> <p>This applies to all studies with surfacic image visualization (e.g., "Pseudo-color view" on Surface studiabiles, "Grid view" on Multi-channel image studiabiles, "View of a force volume", "View of a hyperspectral image", etc.)</p>
Zoom in absolute value (XY) synchronization	<p>The image zoom level and position (in metric unit) can be linked between studies. This is particularly useful with different visualizations of the same sample with common coordinates system.</p> <p>This applies to all studies with surfacic image visualization (e.g., "Pseudo-color view" on Surface studiabiles, "Grid view" on Multi-channel image studiabiles, "View of a force volume", "View of a hyperspectral image", etc.)</p>
Zoom in % (curve) synchronization	<p>The curve zoom level can be linked between studies.</p> <p>This applies to all studies on Profile, Series of profiles, <u>Multi-channel</u> profiles, Spectrum curve, Series of Force curve and IV curve studiabiles.</p>
Element number synchronization	<p>The element number can be linked between studies.</p> <p>This applies to all studies with several elements, on Series of Profiles, Series of surfaces, Series of images, Multi-channel images, Multi-channel profiles, Series of force curves studiabiles.</p>
Force curve synchronization	<p>The force curve number can be linked between studies.</p> <p>This applies to "Force curve analysis" and "Force volume" studies.</p>
Force curve segment synchronization	<p>The displayed segment (approach or retract) can be linked between studies.</p> <p>This applies to "View of a force volume" study.</p>
Spectrum curve synchronization	<p>The spectrum curve number can be linked between studies.</p> <p>This applies to all studies on Hyperspectral image, IV curves and IV spectroscopy image studiabiles.</p>
Spectrum curve (W) synchronization	<p>The position number on the spectral axis can be linked between studies.</p> <p>This applies to the studies "View of a hyperspectral image" and "View of an IV spectroscopy image".</p>
Cutting planes synchronization	<p>The slice numbers of (X, Y and Z) cutting planes on cube can be linked between studies. This applies to the "Pseudo-color view" and 3D view studies on Multi-channel cube studiabiles.</p>
Synchronization manager	<p>The Synchronization manager dialog allows you to create, modify and delete links between studies inside a document. It is available from any study containing synchronizable attributes.</p>
Synchronization management shortcuts	<p>When selecting several studies containing synchronizable attributes, a link button directly opens the Synchronization manager dialog with the corresponding selected studies.</p>
Link icon in the study	<p>If the selected study is linked to another study in the document, a link icon is visible in the top right corner.</p>
	<h2>Profilometry features</h2>
Curve export in the "Slope distribution" study	<p>The slope distribution values can now be exported to a text file from the "Slope distribution" study. This applies to Surface and Surface + image studiabiles.</p>
Display of parameters in "Rk (Sk) parameters" study	<p>In the "Rk (Sk) parameters" study, the display of parameters in the table below the curve, and the settings dialog, are now identical to the ones of the "Parameters table" study. More pre-processing settings are thus available (e.g., microroughness), and more information can be displayed (e.g., warnings).</p> <p>This applies to the "Rk parameters" study on Profiles and Series of profiles studiabiles and to the "Sk parameters" study on Surface, Surface-image, Multi-channel Images and Series of surfaces studiabiles.</p>
Automatable exclusion zones in the "Level" operator on Profiles	<p>Exclusion zones in the "Level" operator on Profile studiabiles, can now be defined in metric units, in relative or in absolute coordinates. Result pickers can be used in automation contexts.</p>
Fine spacing values for the 'Circular analysis' in Contour study	<p>The 'Circular analysis' tool on a portion of a closed Profile studiabile now accepts values with a precision of 0.1 degree.</p>
Frequency index in "Frequency spectrum" study on Profiles	<p>The frequency index is now a separated cursor parameter in the "Frequency spectrum" study on Profile studiabiles.</p>

Homogenization in the “Level” and “Retouch points” operators on Profiles	The interface for units’ choice has been homogenized with “Extract profiles” operator in the “Level” and “Retouch points” operators on Profile and Series of profiles studiabiles (% , points, metric unit, and metric unit in absolute values).
Homogenization of operator dialogs	A few last operators have been redesigned to conform to the operator’s dialog interface guide. Profile or Series of profiles: “Extract area”, “Convert to sliding profiles”, “Concatenate two profile”, “S-filter”. Series of surfaces: “Extract transversal profile”, “Filter using PCA”.
	<b>Shell and Point cloud features</b>
New operator “Stitch together in 3D space”	The “Stitch together in 3D space” operator now allows you to automatically assemble Surface (and Surface + image) studiabiles with Point cloud studiabiles, using recognizable points in the overlapping zone.
Automatic fit with partial Shell in “CAD compare” study	The pre-fit function is now compatible with a partial Shell in the “CAD compare” study on Shell. This allows the user to compare a partial shell (actual data (e.g., measured shell)) with the CAD model (nominal model) that represents the entire work piece. It is an alternative to the manual mode, which is slower and requires the user to locate the right critical points.
New “Fill holes” operator on Shells	The new “Fill holes” operator on Shell studiabiles reconstructs the missing parts of a mesh. Two filling options are available: One for covering relatively flat areas (Relatively planar holes) and the other for areas with curvature (Highly curved holes). It is possible to fill only holes that are smaller than a particular area.
Simplification of the “Mesh the point cloud” operator	The dialog box of the “Mesh the point cloud” operator has been simplified and optimized: several settings previously available are now automatically calculated from the Cloud geometry. Calculation is now faster.
Export Point cloud to PLY	It is now possible to export a point cloud in PLY format.
	<b>Spectroscopy features (for Spectroscopists or SPM users)</b>
Exponential fit in “Peak fitting analysis” study on spectra	‘Single exponential’, ‘Stretched exponential’, ‘Double exponential’ curve and ‘Logarithmic’ curve fitting are now available in the “Peak fitting analysis” study on spectra. In particular, it can be used to study time decay when the W axis represents time. It applies to Spectrum curve and Hyperspectral image studiabiles.
Cursor coordinates in Hyperspectral images and IV spectroscopy images	All studies on Hyperspectral image studiabiles now display homogenized XY cursor coordinates. Coordinates of the cursor can be displayed in absolute coordinate, and in points. The current signal name can also be displayed. It also applies to all the studies on IV spectroscopy image studiabiles.
Position of extracted line of spectra	The curve position in Spectrum curve studiable, after the extraction of a line of spectra in the “Extract series of spectrum curve” operator is now stored as a T axis value and renamed Position of the spectrum curve. It starts from 0 (it previously was coordinates on the source “View of a hyperspectral image” study). This also applies to IV curve studiabiles.
Proportion kept in “View of a hyperspectral image” study	The proportion of the spectra and the image sizes are now kept when resizing the “View of a hyperspectral image” study. The proportion is also kept in full screen mode.
“Use spectral bands” operator on IV spectroscopy images	The “Use spectral bands” operator has been adapted to IV spectroscopy image studiabiles (it was already available on Hyperspectral image studiabiles). It can create colorized maps using user-defined color assigned to values (Area, FWHM, Max, Max amplitude, Max position) calculated on bands in the W axis.
	<b>New Mountains® Products</b>
New MountainsSPIP® Nanospectral Starter and Expert products	The MountainsSPIP® range is extended with the addition of the MountainsSPIP® Nanospectral Starter and MountainsSPIP® Nanospectral. This is destined for users working on both SPM and Spectral technologies (e.g., nano-IR and TERS). This completes the MountainsSPIP® products: MountainsSPIP® Starter, MountainsSPIP® Expert, MountainsSPIP® Academy and MountainsSPIP® Premium.

New MountainsSEM® Image Analysis product	The MountainsSEM® Image range is extended with the addition of the MountainsSEM® Image Analysis product. It is specifically aimed at users performing 2D SEM image analysis, and offers features such as semi-automatic object colorization, particle analysis and correlative analysis with EDS maps. This completes the MountainsSEM® range: MountainsSEM® color, MountainsSEM® Expert and MountainsSEM® Premium.
Four-quadrant reconstruction improvement	The reconstruction of topography from the 4 images of a 4-quadrants BSD detector has been improved. In particular, it gives better results on geometrical features. Previous methods are kept for compatibility.
	<b>Updates and translations for Interface &amp; Reference Guide</b>
User interface	New texts related to new features have been added to the user interface (in English). They have been translated into all available languages: French, German, Italian, Spanish, Japanese, Chinese, Polish, Korean, Brazilian Portuguese, Russian. Note: A complete retranslation into Japanese is in progress. This means that the style and vocabulary might not be homogeneous for the moment.
Reference Guide	The Reference Guide has been updated with the descriptions of most new main features and improvements (in English). It has been translated into all available languages (French, German, and Japanese). Note: A complete retranslation into Japanese is in progress. This means that the style and vocabulary might not be homogeneous for the moment. You might find some English sentences (in the Japanese Reference Guide).

## Bug corrections (A and B type)

	Type	Bug Description
MNT-10391	A	The software may crash if you filter the tree structure of a composite (Surface+image, Multi-channel image, etc.) studiable by name in the studiable explorer panel.
MNT-10835	A	The Ssw parameter (dominant wavelength) calculation on surface studiabiles according to ISO 25178 can be incorrect on surfaces having little or no dominant wavelength.
MNT-11045	A	The software may crash when opening the “3D reconstruction using three images” operator on Image studiabiles.
MNT-11127	A	A crash can occur when opening the “Apply mask of non-measured points” operator on Surface, Surface + image, Multi-channel image studiabiles.
MNT-11402	A	Values in the “Table of results” study may be missing or incorrect in the result of the “Fit an asphere” operator on Surface and Profile studiabiles.
MNT-11507	A	The 3D view of the generated Shell studiable is no longer displayed in the “CAD compare” study when reloading older v10 documents.
MNT-4171	B	Changing the rendering mode to multi-selection on different studiable types in the 3D view study may result in invalid rendering in one of the selected studiabiles.
MNT-8355	B	The flat area is not respected when applying the “3D reconstruction using four quadrant images” operator on Image studiabiles in certain particular cases.
MNT-10520	B	The parameters of the “Sk parameters”, “Rk parameters” and “Parameters table” studies on Surface and Profile studiabiles are not calculated when using an ‘F-Operator’ of type ‘Absolute Total least squares sphere (Absolute TLSSP)’ or ‘Total least squares circle (TLSCI)’.
MNT-10730	B	The “Add/remove image” operator on Series of images studiabiles does not display the studiabiles in the Available studiabiles section of the dialog box if the loaded data is very large.
MNT-10807	B	It is not possible to move between pages in a document by scrolling with the mouse wheel or using the scroll bar with the mouse if the [Page by Page] button is activated.
MNT-10886	B	Modifying the channel colors of a Multi-channel image studiable that is not a root studiable does not result in the colors being modified on the root studiable.

MNT-11021	B	Zooming using a rectangular shape in a “Grid view” study on Series of surfaces studiabes does not display the correct view of the surfaces.
MNT-11036	B	The results from the “Result manager” of a document containing a “Result calculator” are incorrect when the document is reloaded.
MNT-11046	B	The software may crash when adding a “Resample” operator before a “Scale the image” operator on Image studiabes in the workflow in a particular case.
MNT-11065	B	Statistical studies on Surface, Surface + image, Image and Multi-channel image studiabes, using a class from a “Particle analysis” study as a filter, become empty if a class is renamed in the Classification dialog box of one of the studies in the statistical analysis.
MNT-11088	B	Results filtered in the Result manager may be incorrectly exported, as the filter can be incorrectly applied, particularly in an automated environment.
MNT-11089	B	Loading a Shell studiabe in STL format does not work.
MNT-11097	B	Operator dialog boxes can be hidden if the user previously had 2 screens and only one is currently available.
MNT-11112	B	Duplication of an “Advanced contour analysis” study (Ctrl+D) on Profile or Contour profile studiabes does not always work properly.
MNT-11130	B	The W-axis unit is incorrect if the Apply Jacobian intensity correction option is selected in the “Convert W-axis” operator on Spectrum curve studiabes.
MNT-11132	B	The base line height is incorrect when selecting the Average the curve option in the “Extract series of spectrum curves” operator dialog box on Hyperspectral image studiabes.
MNT-11138	B	All channels of studiabes in ZMG format are not always loaded.
MNT-11142	B	Opening the Peak fitting properties dialog box in the “Peak fitting” study on ‘Hyperspectral image studiabes can affect which curve is displayed.
MNT-11146	B	The Peak fitting properties dialog box in the “Peak fitting” study on Hyperspectral image studiabes does not always display properties if the Hyperspectral image studiabe contains non-measured points.
MNT-11149	B	Mountains® may use commas when dealing with real values instead of dots, depending on the regional settings of the host application, when running the software from a third-party application.
MNT-11261	B	The ‘V-groove analysis’ tool in the “Advanced contour analysis” study does not work if any tolerance is set when it is created.
MNT-11299	B	F-operators are not applied on studiabes used for calculations of addon parameters.
MNT-11302	B	It is not possible to modify the palette of the 3D Result view in the “Map local properties” operator on Series of surfaces studiabes.
MNT-11309	B	It is not possible to export the Abbott curve data to a text file in the “Sk parameter” and “Rk parameters” studies using the [Export curve] button.
MNT-11318	B	The settings in the Special options dialog of the “Scale sensitive fractal analysis” study on Surface, Series of surfaces and Image studiabes are not taken into account in the management of the study settings.
MNT-11328	B	The export of the numerical results to a text file in CSV format when applying a template or when using a command file is erroneous if a semi-colon is used in the results.
MNT-11334	B	The ‘Calculate line width roughness’ tools do not work when the selected segments are parallels in the “Advanced contour analysis” study.
MNT-11392	B	Inserting a “Result calculator” into a document does not generate an error message when being used in a product that does not contain this function. Affects demo and free trial licenses only.
MNT-11399	B	Some translations for form removal (F-operation) are missing from the Parameters table dialog box on Profile studiabes.
MNT-11400	B	Some advanced calibration options are not translated in the “3D reconstruction using four quadrant images” operator on Image studiabes.
MNT-14111	B	The points are reversed in Y in the 3D view study on Multi-channel cube studiabes.
MNT-11452	B	The ‘S-filter (As)’ filter is not applied on Profile or Surface studiabes used by addon parameters even when requested.
MNT-11471	B	The channels are not correctly displayed when applying the “Threshold” operator on a Multi-channel image studiabe if some channels are flat.

MNT-11472	B	The histogram of heights is not correctly displayed in the color scale on Multi-channel image studiable if some channels are flat.
MNT-11506	B	The pre-alignment of the Shell studiable in the "CAD compare" study is not preserved when the study is copied and pasted or when the document is saved and then reloaded.
MNT-11512	B	The generated Shell studiable is not redisplayed in the "CAD Compare" study when undoing a previous selection of the [Generate Shell and Deviations] button in the study.